


# HT60-18X(N)

**SINGLE GLASS TOPCON PV MODULE**  
**510-530W**

**DESIGNED FOR AUSTRALIA**  
**MODULE EFFICIENCY UP TO 23.9%**



## FEATURE



Half-cut cell technology reduces internal power loss, improves power production and provides excellent heat dissipation to avoid hot spots.



**30 Year** product warranty for rooftop installations  
**15 Year** for ground mounted.



**30 Year** power output warranty.

## EL Tested

High quality control using double EL tests to ensure reliability and avoid microcracks.



Certified to withstand extreme mechanical load 5400 Pa positive and 2400 Pa negative. 25mm hailstone at the speed of 23m/s.

## TOPCon

Optimised Multi-Busbar (MBB) for maximum light absorption, lower resistance and improved current collection for enhanced reliability.



Designed for high voltage systems of up to 1500 VDC, increases string length and saves on BoS costs.



All modules sorted and packaged by amperage reducing mismatch losses by average of 2% to enhance system output.


## AntiPID

Excellent Anti-PID performance resulting in low power degradation and a high energy yield.

## Low Degradation Rate

0.4% annual degradation rate over 30 year power output.

## WARRANTY



## COMPREHENSIVE AND FIRST-RATE CERTIFICATION SYSTEM

IEC 61215, IEC 61730 Latest Standard  
ISO 9001, ISO 14001, ISO 45001 and SA8000.  
Strict quality control of the highest international standards.



**MULTIWAY+**  
BETTER CHOICE FOR HIGHER EFFICIENCY!

**HT60-18X(N)**  
510W / 515W / 520W / 525W / 530W

### ELECTRICAL CHARACTERISTICS (STC)

| Module Type                          | HT60-18X(N)    |        |        |        |        |
|--------------------------------------|----------------|--------|--------|--------|--------|
| Maximum Power (Pmax)                 | 510W           | 515W   | 520W   | 525W   | 530W   |
| Open Circuit Voltage(Voc)            | 43.7V          | 43.8V  | 44.0V  | 44.2V  | 44.4V  |
| Short Circuit Current(Isc)           | 14.79A         | 14.87A | 14.95A | 15.03A | 15.11A |
| Maximum Power Voltage(Vmp)           | 36.8V          | 37.0V  | 37.2V  | 37.4V  | 37.6V  |
| Maximum Power Current(Imp)           | 13.87A         | 13.93A | 13.99A | 14.05A | 14.11A |
| Module Efficiency                    | 23.0%          | 23.3%  | 23.5%  | 23.7%  | 23.9%  |
| Power/Voc/Isc Measurement Tolerances | ±3%/±5%/±5%    |        |        |        |        |
| Maximum System Voltage               | 1500V DC (IEC) |        |        |        |        |
| Maximum Series Fuse Rating           | 30A            |        |        |        |        |
| Operating Temperature                | -40°C to +85°C |        |        |        |        |

STC: AM 1.5, Irradiance 1000W/m<sup>2</sup>, module temperature 25°C


### ELECTRICAL CHARACTERISTICS (NMOT)

| Module Type                | HT60-18X(N) |        |        |        |        |
|----------------------------|-------------|--------|--------|--------|--------|
| Maximum Power(Pmax)        | 388W        | 392W   | 395W   | 399W   | 403W   |
| Open Circuit Voltage(Voc)  | 42.0V       | 42.0V  | 42.2V  | 42.4V  | 42.6V  |
| Short Circuit Current(Isc) | 11.92A      | 11.98A | 12.05A | 12.11A | 12.18A |
| Maximum Power Voltage(Vmp) | 35.3V       | 35.5V  | 35.7V  | 35.9V  | 36.1V  |
| Maximum Power Current(Imp) | 10.99A      | 11.04A | 11.06A | 11.11A | 11.16A |


NMOT: Irradiance 800W/m<sup>2</sup>, ambient temperature 20°C, wind speed 1m/s

|  |   |           |
|--|---|-----------|
| Nominal Module Operating Temperature(NMOT) | 43 ± 2°C  |           |
| Temperature Coefficient of Pmax            | γ(PM)   | -0.31%/°C |
| Temperature Coefficient of Voc             | β(Voc)  | -0.25%/°C |
| Temperature Coefficient of Isc             | α(Isc)  | 0.046%/°C |
| Solar Cells                                | Monocrystalline                                       |           |
| No. of Cells                               | 120 (6x20)  |           |
| Dimensions                                 | 1952mm x 1134mm x 30mm                                |           |
| Weight                                     | 23.5 kg   |           |
| Glass                                      | High light transmittance coated tempered glass        |           |
| Frame                                      | Anodised aluminum alloy                               |           |
| Junction Box/Connectors                    | IP68 / PV-HT005-01 HT-SAAE product / Stäubli MC4      |           |
| Cable                                      | 4mm <sup>2</sup> (IEC) length: (+) 1200mm, (-) 1200mm |           |
| Fire Rating                                | IEC Class C   |           |
| Packaging Configuration                    | 36 pcs/box: 864 pcs/ 40' HQ Container                 |           |

### DIMENSIONS OF PV MODULE (MM)



### IV CURVES



**Shanghai Aerospace Automobile Electromechanical Co., Ltd.**  
Shanghai Aerospace Innovation and Entrepreneurship Center  
No. 3883, Building 1, Yuanjiang Road, Minhang District  
Shanghai, China 201108

**Australia office**  
Level 45, 680 George St, Sydney NSW 2000

Website: [www.ht-saae.com.au](http://www.ht-saae.com.au)

**Made in China**

Module recycling should be carried out by professionals.

Copyright©2024V2 Specifications are subject to change without further notification.

Only available in Australia